

# DEF TRANSPORT TOTE

## PORTABLE DIESEL EXHAUST FLUID SYSTEM DESIGNED FOR SERVICE IN COLD WEATHER ENVIRONMENTS

Designed to fit in a standard truck bed, the components of this portable DEF skid are protected under a lockable, weather sealed door.

- 50 Gallon Poly DEF Tank
- 2-in-1 DEF Pumping System
- Compliant with ISO 22241 Standards
- Heater Kit - Heater, Regulator, Thermostat, Foil Covered Foam Installation and Mounting Bracket for LP Tank (*LP Tank Not Included*)



### Loading

The skid is easily loaded and secured using the same lift points. Everything is quickly accessible from the driver side of the truck bed.

### Pumping

Unlike other portable DEF units, you don't need to move the pump between filling and dispensing. Just attach the Micro-Matic® coupler or nozzle to the hose, set the flow direction and turn the pump on.

### Savings

Thunder Creek's patent-pending 2-in-1 DEF pumping system allows you to fill and dispense using just one pump. You don't have to purchase a separate DEF transfer pump to fill our DEF Transport Tote!

### Purity

Most importantly, the Thunder Creek system maintains a completely closed loop system, so exposure to contamination is minimized.



**CALL: [FlowMaxDPF.com](http://FlowMaxDPF.com)  
at 613.342.9222**

### WHAT HAPPENS WHEN DEF GETS CONTAMINATED

- Increases DEF consumption in the equipment
- Loses its effectiveness to remove nitrogen oxides from engine exhaust
- Can cause malfunctions with the SCR system
- Can cause the equipment engine to shut down
- Can damage equipment
- Can void manufacturer's equipment warranty



INSULATED

# DEF TRANSPORT TOTE

WITH THERMOSTAT REGULATED HEAT PROTECTION

## FITS IN A STANDARD TRUCK BED

### Diesel Exhaust Fluid (DEF) Tank

- 50 Gallon (190 l) Specialized Poly Tank for DEF

### DEF Pumping System

- Industrial Grade 12V DEF Pump
- 20' (6.1 m) x 3/4" (19 mm) Hose
- Interchangeable
  - Auto Trip Nozzle
  - Micro-Matic® RSV Fill Coupler
- 6' Power Cables
- 2-in-1 DEF Pumping System (patent pending)

### Outer Enclosure

- 14 Gauge Steel
- Multiple Lift Points for Easy of Handling
- Sight Glass on Side of Tote
- Lockable, Weather-Sealed Door w/ Chrome Handle
- Dual Coat Polyurethane Gray Paint



25.9" (0.7 m)

26.15" (0.7 m)



44.3" (1.1 m)

Weight- 188 lbs. Empty (85.3 kg)  
638 lbs. Full (289.4 kg)

### Add-On Options

- Digital DEF Meter
- **Skid Base- NEW!**



DEF Transport Tote

Optional Skid Base

## DEF MADE EASY

Dealing with DEF is easy with Thunder Creek. Our patent-pending 2-in-1 pumping system allows you to fill and empty the portable DEF tank using just one pumping system. This closed loop system ensures the purity of the DEF is maintained to safeguard your equipment and SCR system.

### Fill Your DEF Transport Tote

- Set the Fill/Empty valve to "Fill"
- Attach the MicroMatic® coupler to the DEF hose.
- Connect the coupler to the IBC tote valve.
- When activated the DEF pump pulls fluid from the tote filling the DEF Transport Tote.



### Dispense DEF into Your Equipment

- Set the Fill/Empty valve to "Empty."
- Attach the DEF nozzle to the DEF hose.
- Insert the nozzle into your equipment's DEF tank.
- When activated, the system pumps fluid from the trailer into your equipment.

CALL: [FlowMaxDPF.com](http://FlowMaxDPF.com) @ 613.342.9222 for Pricing